



## Slipway Trailer

## SW20

5

10

20

30

The Hydrotrans hydraulic boat trailer is designed to launch and recover boats on a slipway, transport the boats over land and park them in a storage or work area.

### Slipway trailer

The Hydrotrans SW20 can be pulled by a reach truck or an agricultural tractor. It uses the hydraulic capacity of the tow vehicle for all the hydraulic functions. The boat is lifted by 4 hydraulic pads with soft pads on them to avoid damaging the hull. The front of the boat is supported by the crossbeam with also a soft pad on it to avoid damage. For sailboats an adaptor is available.

### Trailer frame

The width of the trailer frame and the height are hydraulic adjustable. The pads and drawbar are hydraulically adjustable.

### Hydrotrans

#### Lift & carry equipment

Windas 9

8441 RC Heerenveen

The Netherlands

Tel: +31 858 782 510

Fax: +31 848 833 774

Email: [info@hydrotrans.nl](mailto:info@hydrotrans.nl)

[www.hydrotrans.nl](http://www.hydrotrans.nl)





## SW 20

The Hydrotrans SW20 slipway trailer is also suitable for transporting boats on T-cradle's. The solid or pneumatic tires of the SW20 offers optimal security through any terrain capable of carrying the load.

### Technical specifications

Open U-designed frame with adjustable width, height and length.

<b>Capacity</b>	20.000 kg
<b>Wheels</b>	air tires
<b>Drawbar</b>	1,0 mtr. extendable
<b>Pads</b>	4 pads 900x300 mm
<b>Hydraulic cylinders</b>	high quality cylinders with safety valves built-in
<b>Paint system</b>	shot blasted and total 2 coats epoxy primer and 2 coats 2 component topcoat

### Delivery

All Hydrotrans products are designed, manufactured and tested according to the European Conformity of Machines (CE) and are delivered with a comprehensive manual in English language. The standard warranty period is 1 year after delivery.

### Dimensions

<b>Lifting height frame</b>	540 mm
<b>Lifting height pads</b>	300 mm
<b>Height on pads</b>	740-1630 mm
<b>Total length</b>	972-1182 mm
<b>Total width</b>	2620-4000 mm
<b>Inside width</b>	1100-2480 mm