



Slipway Trailer SW30-35

The Hydrotrans hydraulic boat trailer is designed to launch and recover boats on a slipway, transport the boats over land and park them in a storage or work area.

Slipway trailer

The Hydrotrans SW30-35 can be pulled by a reach truck or an agricultural tractor. It uses the hydraulic capacity of the tow vehicle for all the hydraulic functions. The boat is lifted by 4 hydraulic pads with soft pads on them to avoid damaging the hull. The front of the boat is supported by the crossbeam with also a soft pad on it to avoid damage. For sailboats an adaptor is available.

Trailer frame

The width of the trailer frame and the height are hydraulic adjustable. The pads and drawbar are hydraulically adjustable.

Hydrotrans

Lift & carry equipment

Windas 9
8441 RC Heerenveen
The Netherlands

Tel: +31 858 782 510
Fax: +31 848 833 774
Email: info@hydrotrans.nl

www.hydrotrans.nl





SW 30-35

The Hydrotrans SW30-35 slipway trailer is also suitable for transporting boats on T-cradle's. The solid or pneumatic tires of the SW35 offer optimal security through any terrain capable of carrying the load.

SAE specifications and warranty

The Hydrotrans SW30-35 is built according to CE-regulations and is tested at the factory before shipment. All Hydrotrans equipment can be built to SAE specifications and carry a 1 year warranty.

Technical specifications

Open U-designed frame with adjustable width, height and length.

Capacity	30.000 - 35.000 kg
Wheels	8 solid tires
Drawbar	2,0 mtr. extendable
Pads	4 polyurethane pads 930x320 mm
Hydraulic cylinders	high quality cylinders with safety valves built-in
Paint system	300 Microns total 2 coats epoxy primer and 2 coats 2 component topcoat

Dimensions

Height on pads	765 mm
Height on front	385 mm
Distance between centre of pads	1420-2820 mm
Lifting height frame	500 mm
Lifting height pads	400 mm