



Slipway Trailer

SW30

5

10

20

30

The Hydrotrans hydraulic boat trailer is designed to launch and recover boats on a slipway, transport the boats over land and park them in a storage or work area.

Slipway trailer

The Hydrotrans SW30 can be pulled by a reach truck or an agricultural tractor. It uses the hydraulic capacity of the tow vehicle for all the hydraulic functions. The boat is lifted by 4 hydraulic pads with soft pads on them to avoid damaging the hull. The front of the boat is supported by the crossbeam with also a soft pad on it to avoid damage. For sailboats an adaptor is available.

Trailer frame

The width of the trailer frame and the height are hydraulic adjustable. The pads and drawbar are hydraulically adjustable.

Hydrotrans

Lift & carry equipment

Windas 9

8441 RC Heerenveen

The Netherlands

Tel: +31 858 782 510

Fax: +31 848 833 774

Email: info@hydrotrans.nl

www.hydrotrans.nl





SW 30

The Hydrotrans SW30 slipway trailer is also suitable for transporting boats on T-cradle's. The solid or pneumatic tires of the SW30 offers a comfortable ride through any terrain capable of carrying the load.

Technical specifications

Open U-designed frame with adjustable width, height and length.

Capacity	30.000 kg
Wheels	8 solid tires
Drawbar	2 mtr. extendable
Pads	4 pads 900x300 mm
Hydraulic cylinders	high quality cylinders with safety valves built-in
Paint system	shot blasted and total 2 coats epoxy primer and 2 coats 2 component topcoat

Delivery

All Hydrotrans products are designed, manufactured and tested according to the European Conformity of Machines (CE) and are delivered with a comprehensive manual in English language. The standard warranty period is 1 year after delivery.

Dimensions

Height on front	385 mm
Distance between centre of pads	1420-2820 mm
Lifting height frame	670 mm
Lifting height pads	400 mm
Height on pads	780-1270 mm
Total length	1004-1214 mm
Total width	2890-4270 mm
Inside width	1130-2510 mm