



Slipway Trailer SW50

The Hydrotrans hydraulic boat trailer is designed to launch and recover boats on a slipway, transport the boats over land and park them in a storage or work area.

Slipway trailer

The Hydrotrans SW50 can be pulled by a forklift, or an agricultural tractor. It uses the hydraulic capacity of the tow vehicle for all the hydraulic functions. The boat is lifted by 6 hydraulic cylinders with durable rubber pads on them to avoid damaging the hull. The front of the boat is supported by the crossbeam also with a rubber pad on it to avoid damage. For sailboats an adaptor is available, and an adaptor for catamarans is also available.

Trailer frame

The width of the trailer frame and the height are adjustable.

Hydrotrans

Lift & carry equipment

Windas 9
8441 RC Heerenveen
The Netherlands

Tel: +31 858 782 510
Fax: +31 848 833 774
Email: info@hydrotrans.nl

www.hydrotrans.nl





SW50

The Hydrotrans SW series trailers are also suitable for transporting boats on T-cradle's. With solid or pneumatic tires, the SW trailer offers optimal comfort through any terrain capable of carrying the load.

SAE specifications and warranty

The Hydrotrans SW25 is built according to CE-regulations and is tested at the factory before shipment. All Hydrotrans equipment can be built to SAE specifications and carry a 1 year warranty.

Technical specifications

Open U-designed frame with adjustable width, height and length.

Capacity	50.000 kg
Wheels	16 solid tires
Drawbar	4,0 mtr. extendable
Pads	6 polyurethane pads 930x320 mm
Hydraulic cylinders	high quality cylinders with safety valves built-in
Paint system	300 Microns total 2 coats epoxy primer and 2 coats 2 component topcoat

Dimensions

Height on pads	935 mm
Height on front	470 mm
Distance between centre of pads	1580-3080 mm
Lifting height frame	500 mm
Lifting height pads	450 mm